

BIOS Release Notes

TITLE

SUBJECT: MZ73-LM0 BIOS Release Notes version F15
System: MZ73-LM0-000

About This Release

Build Date: 2023/09/07
BIOS Checksum: 0xBF00E3E1 (32M)
Release Owner: Iris.Chang

BIOS Components/Contents

Processor stepping(s) supported: AMD Genoa Processors
System hardware configurations supported: MZ73-LM0-000
PCB Version: 1.0
Microcode updates versions:

CPUID	Family	Microcode Update ID
Genoa B0	Family 19h Model 10-1Fh	0x0A101020
Genoa B1	Family 19h Model 10-1Fh	0x0A10113E
Genoa B2	Family 19h Model 10-1Fh	0x0A10123E
Bergamo A0	Family 19h Model 10-1Fh	0x0AA00009
Bergamo A1	Family 19h Model 10-1Fh	0x0AA00116
Bergamo A2	Family 19h Model 10-1Fh	0x0AA00212

IPMI support:
AMI Kernel version: 5.27_GenoaCrb_0ACQT022
AGESA PI version: GenoaPI 1.0.0.9
OPROM version:

OPROM	Version
AST2600	1.12.00

Installation Notes

IMPORTANT NOTES:

1. Please extract the MZ73-LM0_F15.zip to a bootable diskette that use FAT/FAT32 format

BIOS UPDATE INSTRUCTIONS FOR EFI Shell:

1. Insert USB flash drive to system for BIOS upgrade.
2. Power on system and boot to Build-In Shell.
3. Enter your USB filesystem, like "fs0:" or "fsx:", "x" is your USB filesystem number
4. Execute F.nsh for bios update
5. After bios flash finish, system must Power-Off to have the changes take effect.

BIOS Release Notes

BIOS UPDATE INSTRUCTIONS FOR Windows:

1. Insert bios update USB flash drive.
2. Use Command Shell.
3. Enter \Tool\Win32 and execute f.bat for Windows 32bit.
Or
Enter \Tool\Win64 and execute f.bat for Windows 64bit.
4. After bios flash finish, system must Power-Off to have the changes take effect.

BIOS UPDATE FOR Easy BIOS Refresh:

1. The system supports remotely update BIOS if BMC existent.
2. Please download the Easy BIOS Refresh User Guide from Gigabyte website, target system support page.

BIOS Version CHECK INSTRUCTIONS:

1. Power on system and press during POST
2. The bios version shows on the first main page

Known Issues/Workarounds

Issues fixed in this version

F15

1. Remove U2_P1_G0A & U2_P1_G0B present function.
-

F14

1. Fixed system reboot when error hold on.
 2. Fixed yellow bang in windows.
-

F13

1. Adjust U2_P1_P0A and U2_P1_P0B support behavior.
-

F12

1. MOIO Item U2_P1_P0 modify to U2_P1_P0A & U2_P1_P0B .
-

F11

1. Adjusted BMC Watch Dog timer.
 2. Optimize Chelsio cards compatibility.
-

F10

1. Support Present function.

BIOS Release Notes

F09

1. Update Inventory Mapping system.
 2. Fixed COM Port mouse is not working.
 3. Added DIMM Manufacturer ID 0x1A08.
 4. Fixed NVME LED control failed.
 5. Fixed SATA LED Control failed.
 6. Adjust the display order of NVME devices list.
 7. Support PCIe Slot1/2 x4x4x4x4 capability.
-

F08

- 1.Support PCIe Slot1/2 x4x4x4x4 capability for PCB VER.2.0.
-

F06

1. Updated AGESA 1.0.0.5.
-

F05

1. Modify setup menu sata info back to no reversal to match HW(1.0) design.
-

F04

1. Fixed sata info on setup menu & WebbUI.
-

F03

1. Change slsas slot1.2 default funtion.
 2. Fixed M.2 no show issue on setupmenu.
 3. 9555 write low.
-

F02

1. Add MZ73-LM1 System.
 2. Update Agesa1003.
 3. remove U2_P1_P0 X16.
-

F01

1. First Release.
-